Test Jumper Kit (TJK)





Applications

- Link-loss Testing
- Continuity Testing
- Equipment Calibration
- Product Demonstrations
- Training Aid
- Research and Development Reference Fiber

Key Features & Benefits

- Rugged Case Protects Jumpers During Use and Transit
- Lightweight Unit
- Variety of Fiber and Connector Types Available
- Duplex and Simplex Configurations Available

Overview

OptiConcepts Test Jumper Kits offer convenience by providing all necessary reference jumpers and adapters required for connector testing in one unit. The kits are housed in a compact, light-weight, rugged carrying case. Various connector styles and fiber types are available. Our Test Jumper Kits include simplex and duplex options for a complete testing solution.

Specifications

Fiber Type: Single-mode, Multimode 50/125um Laser Optimized Capable, Multimode 62.5/125um Jumper Length: 3 meters (10 ft)

Temperature Range: -40° to 122°F (-40° to 50°C)

Humidity: 0 to 95%

Connector Type: FC, SC, ST, LC, MTRJ – Ultra and Angled Varieties (other styles available upon request)

Test Jumper Kit (TJK)

Ordering Information

TJK Standard Part Number Configuration

TJK-ABC-D

[PN Example: TJK-11S-S – FC/FC, Single-mode Simplex]

A) Test Equipment Connector Type

FC=I FC Angle=2 SC=3 SC Angle=4 ST=5 LC=6 MTRJ=7

B) Second Connector Type

FC=I FC Angle=2 SC=3 SC Angle=4 ST=5 LC=6 MTRJ=7

C) Fiber Type

Single-mode=S Multimode 50um Laser Optimized=5 Multimode 62.5um=6

D) Fiber Count

S=Simplex D=Duplex

Quality Statement

OptiConcepts is committed to providing high quality, easy to use test equipment by integrating customer needs into world class engineered products and systems.

