



## HD 37AB17D, HD 37B17D

### DATALOGGER

#### RELATIVE HUMIDITY - TEMPERATURE - CO - CO<sub>2</sub>

**HD37AB17D** and **HD37B17D** instrument are **data loggers** able to measure and memorize simultaneously the following parameters:

- Relative Humidity **RH**
- Environment temperature **T**
- Carbon monoxide **CO** (only **HD37AB17D**)
- Carbon dioxide **CO<sub>2</sub>**

**HD37AB17D** and **HD37B17D** instruments have the ability to investigate and monitor the indoor air quality.

Typical applications include checking air quality inside buildings occupied by people (schools, hospitals, auditoria, canteens, etc.); and work places to optimize the comfort and to generally check for small leaks of CO with danger of explosions or fire. This analysis allows the management of conditioning plants (temperature and humidity) and ventilation (recycle air/hour) in order to reach a double purpose: getting a good quality of the air in accordance with ASHRAE and IMC regulations and energy saving.

**HD37AB17D** and **HD37B17D** are instruments which are very useful to fight the so-called syndrome of sick building.

**RH** (Relative Humidity) measurement is obtained with a capacitive sensor.

**T** temperature is measured with a high precision NTC sensor.

The **CO** measurement (Carbon monoxide, only for **HD37AB17D**) is made by an electrochemical cell with two electrodes indicated to detect the presence of Carbon monoxide, lethal for men, in his living or working environment.

The **CO<sub>2</sub>** measurement (Carbon dioxide) is obtained with a special infrared sensor (NDIR technology: Non-Dispersive Infrared Technology) that, thanks to the use of double filter and a special measurement techniques, guarantees accurate and stable measurements over time. The infrared sensor is equipped with a protection membrane which provides protection from dust particles and aggressive air agents to assure the sensor's long life.

**HD37AB17D** and **HD37B17D** are **data loggers** able to memorize the detected measurements at an interval set by the user.

**HD37AB17D** and **HD37B17D** are connected to the PC by **USB** input.

**DeltaLog13** communication **software** via the USB port, designed to perform data transfer, data collection and recording and printing of all the instrument parameters

and stored measurements. In addition the software allows the calibration adjustments of the RH, CO (only HD37B17D) and CO<sub>2</sub> sensors.

Using appropriate procedure, the Software DeltaLog13 can evaluate the parameter **% OA** (percentage of external air), according to the following formula:

$$\%OA = \frac{X_r - X_s}{X_r - X_0} \cdot 100$$

whereas:

**X<sub>r</sub>** = CO<sub>2</sub> in return air

**X<sub>s</sub>** = CO<sub>2</sub> in the outlet air

**X<sub>0</sub>** = CO<sub>2</sub> in the external air

The power supply of the instrument is provided by a 2 Ni-MH **rechargeable** batteries package (code BAT-20), that that allows 8 hours of continuous working in acquisition mode.

#### Technical Features

|                                      |   |
|--------------------------------------|---|
| Dimensions                           | 275 mm x 45 mm x 40 mm                                    |
| Weight                               | 230 g (batteries included)                                |
| Materials                            | ABS   |
| Mains power supply (code SWD06)      | Batteries charger <b>100-240Vac/6Vdc-1A</b>               |
| Batteries                            | Package with 2 rechargeable batteries 1.2V type AA (NiMH) |
| Autonomy                             | 8 hours of continuous working in measurement mode         |
| Current absorbed with instrument off | 200µA   |
| Instrument working temperature       | 0°C ... 50°C  |
| Working relative humidity            | 0%RH ... 95%RH no condensation                            |
| Temperature / Storage humidity       | -25°C ... +70°C / 10%RH ... 90%RH no condensation         |
| Safety of the stored data            | Unlimited   |

#### Connections

|   |  |
|---|--|
| USB interface                               | USB 2.0 cable B type Baudrate 460800   |
| Charger Batteries power supply (code SWD06) | 2 - poles connector (positive at the centre)<br>Output voltage: <b>6Vdc</b><br>Maximum current: 1600mA (9, 60 VA Max). |

#### Measuring rate

1 sample every three seconds

#### Storage capacity

20000 Records  
Every record includes the following:  
- date and time  
- measurement of the carbon dioxide (CO<sub>2</sub>)  
- measurement of the carbon monoxide (CO- only HD37AB17D)  
- measurement of the relative humidity (RH)  
- measurement of the temperature (T)



## Logging interval

selectable within: 3,6,12,15,30,60 seconds,  
2,3,4,5 minutes

The stored values represent the average  
value of the samples that are stored every  
three seconds.

## Printing interval

selectable within: 3,6,12,15,30,60 seconds,  
2,3,4,5 minutes

The printed values represent the average  
value of the samples that are stored every  
three seconds.

## Sensor Features

### Relative Humidity RH

Sensor protection

Capacitive sensor

Net filter made of stainless steel (on request  
filter P6 in AISI316 sintered 20µm or filter P7  
in PTFE sintered 10µm)

Measurement range

0...100 % RH

Sensor working range

-40...+80°C

Accuracy

±2% (5÷90%RH) ±2,5% in the remaining range

Resolution

0,1%

Thermal effects

±2% on whole temperature range

Hysteresis and repeatability

1% RH

Response time ( $T_{90}$ )

< 20 sec. (air speed = 2m/sec) without filter

Long term stability

1%/year

### Temperature T

Sensor type

NTC 10KΩ

Measurement range

-40...+60°C

Accuracy

±0,2°C ±0,15% of the measure

Resolution

0,1°C

Response time ( $T_{90}$ )

< 30 sec. (air speed = 2m/sec)

Long term stability

0,1°C/year

### Carbon monoxide CO (only HD37AB17D)

Sensor

Electro chemical cell

Measurement range

0...500ppm

Sensor working range

-5...+50°C

Accuracy

±3ppm+3% of the measured value

Resolution

1ppm

Response time ( $T_{90}$ )

< 50 sec.

Long term stability

5% of the measure/year

Expected life

> 5 years in normal environmental conditions

## Carbon dioxide CO<sub>2</sub>

Sensor

Measurement range

NDIR with a double wave length

0...5000 ppm

Sensor working range

-5...+50°C

Accuracy

±50ppm+3% of the measurement

Resolution

1ppm

Thermal effects

0,1% f.s./°C

Response time ( $T_{90}$ )

< 120 sec. (air speed = 2m/sec)

Long term stability

5% of the measure/ 5 years

## Ordering codes

**HD37AB17D:** The kit consisting of: **HD37AB17D** instrument to measure CO (Carbon monoxide), CO<sub>2</sub> (Carbon dioxide), RH (Relative Humidity), T (Temperature), **DeltaLog13** Software, USB cable code **CP22**, **SWD06** power supply, **BAT-2** batteries pack, instruction manual, carrying case.

**HD37B17D:** instrument to measure CO<sub>2</sub> (Carbon dioxide), CO (Carbon monoxide), RH (Relative Humidity), T (Temperature), **DeltaLog13** Software, USB cable code **CP22**, **SWD06** power supply, **BAT-2** batteries pack, instruction manual, carrying case.

## Accessories:

**VTRAP20:** Instrument tripod, maximum height 270mm.

**SWD06:** 100-240Vac/6Vdc-1A mains voltage power supply.

**BAT-20:** Replacement batteries pack for HD37AB17D and HD37B17D instruments with integrated temperature sensor.

**P5:** Stainless steel grid protection for probes diameter 14, thread M12×1.

**P6:** Sintered stainless steel 10µ grid protection, for probes diameter 14, thread M12×1.

**P7:** 10µ, PTFE protection for probes diameter 14, thread M12×1.

**P8:** Stainless steel and Poca protection for probes diameter 14, thread M12×1.

**HD75:** Saturated solution for testing the Relative Humidity with 75% HR, complete with adapter for probes diameter 14, thread M12×1.

**HD33:** Saturated solution for testing the Relative Humidity with 33% HR, complete with adapter for probes diameter 14, thread M12×1.

**MINICAN.12A:** Cylinder of nitrogen for the calibration of CO and CO<sub>2</sub> at 0ppm. Volume 12 litres. **With adjustment valve.**

**MINICAN.12A1:** Cylinder of nitrogen for the calibration of CO and CO<sub>2</sub> at 0ppm. Volume 12 litres. **Without adjustment valve.**

**ECO-SURE-2E CO:** Spare CO sensor.

**HD37.36:** Kit connection pipe between instrument and MINICAN.12A for the calibration of CO.

**HD37.37:** Kit connection pipe between instrument and MINICAN.12A for the calibration of CO<sub>2</sub>.

